



OFF ROAD

AGRICULTURE

**Our efficiency.
Your edge.**



OFF ROAD

AGRICULTURE

**Our efficiency.
Your edge.**

Index

Introduction	5
The F28 Series	18
The F5 Series	26
The Nef Series	34
The Cursor Series	44
The V Series	52
The Power Pack	62

THE STAGE V CHALLENGE

Technological excellence and product innovation are at the core of FPT Industrial's mission. We have focused our R&D activities in order to become the innovation leader in the agriculture powertrain field and a go-to provider of the most advanced and increasingly sustainable solutions.

Compliance with emission standards comes with minimal impact on vehicle architecture. HI-eSCR is a breakthrough technology bringing vast performance and efficiency benefits. This FPT patent makes the most of a 25-year, 1-million-unit experience.

To comply with Stage V standards, the second-generation HI-eSCR2 system guarantees competitive advantages, including best-in-class performance and low running costs.

FPT's Stage V Solution

- High Productivity
- Reduced operating costs
- "For life" after-treatment systems
- Enhanced reliability
- Maximised uptime

High Performance	Best in class power and torque density.
Low Operating Costs	Best in class fluid consumption. Maintenance-free after-treatment system: no replacement costs over lifecycle.
Ease of Use	Extended service intervals.

Emission Standards Scenario

During the combustion process, the chemical energy of the fuel is converted into mechanical energy. Because of the chemistry of combustion, several pollutants are produced, of which the most harmful are Nitrogen Oxides (NOx) and Particulate Matter (PM).

Since 2011, when Tier4 Interim/ Stage IIIB came into force, many efforts have been made to reduce such pollutants damaging the environment.


Tier4 Final/Stage IV regulation, introduced in 2014, implied a further significant reduction of NOx (~80% Vs. Tier4 Interim/Stage IIIB levels) while PM was not affected by further reductions.

Stage V, the new regulatory step introduced in Europe in 2019/2020 (depending on engine power level), further tightens the limits on PM emissions: admitted PM quantity has been reduced by 40% compared to Stage IV and a new limit has been introduced on the number of emitted particles (Particle Number Limit, PN).

In addition, Stage V regulation involves power ranges which, up until now, have been subject to lighter or no legislation at all in Europe (power ranges below 37 kW or above 560 kW).

Emission Regulations — Roadmap


European non road mobile machinery, agricultural and forestry tractors & usa non road compression & ignition engine emission standards



Legend

After the introduction of Tier4 Final/Stage IV emission limits in 2014-2015, a further regulation re-enforcement will be introduced for European Non-Road applications in 2019 or 2020 depending on power levels.
 Emission Durability Period: 8000 hours, 10 years.
 No new type approval in Europe for existing emission stage permitted in the year before new emission stage introduction

**We innovate constantly.
We increase the benefits for
end users and create value
for the businesses we serve.**



HI-eSCR 2

Tier 4 final/ Stage IV

FPT Industrial's patented HI-eSCR system is able to reduce the NOX levels more than 95%, offering best-in-class conversion efficiency; moreover, thanks to no DPF, the FPT solution is maintenance free and improves productivity by avoiding downtime during operation for filter cleaning or replacement.

Stage V

To maintain the advantages of the unique and unbeaten HI-eSCR technology, FPT Industrial will integrate a maintenance-free filtering device on its SCR catalyst, thus allowing to comply with tightened limits on PM emissions within a compact package.

The HI-eSCR 2 system, applicable for engines above 56 kW and below 560 kW, where different emission limits apply, maintains the same dimensions of the current Tier 4 Final / Stage IV applications, requiring no machine redesign or layout changes to make it easier to comply with the next emission level.

Thanks to optimized combustion, leadership on performance and fuel efficiency is confirmed, while maintenance-free after-treatment ensure low running costs avoiding unplanned downtime.


Benefits

- High performance for increased vehicle productivity.
- No additional complexity and lean design for easier installation and maximum reliability.
- Low operating costs thanks to high efficiency and long service intervals.

By way of continuous technical advantages our state of the art engine range allows our customers to have class leading features, such as minimized total cost of ownership and outstanding performance. Key to the optimization of engine efficiency is EGR-free combustion on NEF and Cursor engine families, together with high cylinder pressure and high injection pressures: engines adopting the latest generation of Common Rail system feature peak nozzle pressures of up to 2200 bar.

To achieve these targets, crankcase and cylinder head design has been improved to ensure increased structural stiffness. An Electronic Control Unit manages engine parameters and guarantees an accurate control of the after treatment system.

Extended service interval, together with a maintenance-free after-treatment solution reduce running cost for end users.




1. Diesel Oxidation Catalyst
 $NO \rightarrow NO_2$
 HC, CO and PM oxidation

2. AdBlue* / DEF Injection
 Hydrolysis \rightarrow
 $NH_3 + CO_2$

3. Selective Catalytic Reduction on filter
 NO and NO_2 reduction by NH_3 to N_2 and H_2O
 PM oxidation with NO_2

4. Clean Up Catalyst
 Residual NH_3 oxidation



Legend

- PM Particulate Matter
- HC Unburnt Hydrocarbons
- NO_x Nitrogen Oxides
- CO Carbon monoxide
- N₂ Nitrogen
- CO₂ Carbon Dioxide
- H₂O Water



Main Components

The whole system is fitted with a network of integrated sensors to control temperature, pressure and NOx levels.

Exhaust gas flow coming from the engine enters the DOC, where NO is oxidised to NO₂, in order to maximize SCR catalyst's efficiency conversion.

The ECU (Engine Control Unit), the brain behind the HI-eSCR 2 system, checks, through integrated sensors network, the amount of Water-Urea (DEF/AdBlue) solution to be injected in the exhaust pipe. To increase the durability of the injector, Dosing Module is cooled by the engine coolant.

The HI-eSCR 2 after-treatment integrates both the filtering device and the SCR in a compact layout, ensuring no layout impact Vs. Stage IV. At the same time as trapping and oxidizing the Particulate Matter, the catalyst converts NOx into Nitrogen (N₂) and water (H₂O) thanks to the chemical reaction of Ammonia (NH₃) generated from DEF/Adblue.

In the end, the integrated CUC eliminates the remaining ammonia (NH₃). The result is a reduction of NOx superior to 95% and the PM levels within Stage V emission limits.



Patents

- Closed loop control with proprietary algorithms and dedicated sensors to provide accurate monitoring of exhaust gas composition and optimized DEF/AdBlue dosing strategy.
- Thermally insulated high turbulence mixer to allow homogeneous DEF/AdBlue evaporation and urea hydrolysis ensuring correct distribution in exhaust gas flow.
- Optimized exhaust gas thermal management to ensure emission compliance in all working conditions.
- All after-treatment components are packaged in a compact and fully enclosed structure, providing flexible layout options to simplify installation on machines.



FPT Off Road Engine Portfolio

STAGE V



THE F28 SERIES


From 37 to 75 kW

Architecture
4 CYL, 2,8 L
displacement.

Torque
Up to 415 Nm.

**After Treatment
System**
Compact HI-eSCR2
(above 55kW).

Service
600 hours service
intervals.




The all new F28 Stage V is a one-engine solution that matches both space and performance-driven applications thanks to enhanced output in a highly compact packaging.

Its versatile design makes F28 ideal for a number of agriculture applications, such as specialized and small utility tractors.

F28 is designed to be multi-power and features a modular architecture — it can run on diesel, natural gas and it is suitable for hybrid applications — providing the best performance in all working conditions and ensuring maximum installation flexibility.

F28



Engine Specifications

Model	Cyl Arrangement Air Handling	Turbocharging	Injection System	Displacement (Liters)	Power			Torque			Emission Standard	Exhaust System
					(kW)	(hp)	(RPM)	(Nm)	(Lb/ft)	(RPM)		
F28	4L/TCA	WG	Common Rail	2,8	37	50	2500	207	153	1400	Tier 4 Final Stage V	EGR+DOC DOC+DPF
F28	4L/TCA	WG	Common Rail	2,8	43	58	2500	250	184	1400	Tier 4 Final Stage V	EGR+DOC DOC+DPF
F28	4L/TC	WG	Common Rail	2,8	55	75	2500	260	192	1800	Tier 4 Final Stage V	EGR+DOC EGR+DOC+DPF
F28	4L/TCA	WG	Common Rail	2,8	55	75	2500	375	277	1400	Tier 4 Final Stage V	EGR+DOC EGR+DOC+DPF
F28	4L/TCA	WG	Common Rail	2,8	75	100	2300	415	306	1500	Tier 4 Final Stage V	EGR+DOC+DPF+SCR

Legend

Preliminary engine data for F36 above 56kW.
Max engine capability indicated for F34
below 56kW.

Air Intake
TCA Turbocharged After Cooled

Turbocharging
WG Fixed geometry turbocharger
with WasteGate valve

Compact Package, Bigger Performance

Compact agriculture equipment requires increasing performance respecting stringent dimension constraints. Therefore, engines are challenged to outperform, maximizing productivity within compact layouts.

The FPT solution for specialized and small utility tractors is the new F28 Stage V, a one-engine solution that matches both space and performance-driven applications thanks to enhanced output in a highly compact packaging.

In line with FPT strategy and commitment to sustainable solutions, F28 features efficient, optimized combustion and has been designed to be Modular and Multipower, for Diesel, natural gas and hybrid applications providing lower operating costs and environmental sustainability.

Lean design, with integrated EGR channel and reduced liner bridge, ensures compactness for easier vehicle installation. A wide range of options is also available, including flywheels, flywheel housings, oil pans and filters.

A highly compact after-treatment solution grants cross-region installation modularity, with a common packaging for Europe Stage V (DOC+DPF) and NAFTA Tier 4 Final (DOC-only).

A full-service package—from maintenance to support—can be tailor-made for every customer and industry.

Key Advantages

	Features	Benefit
Performance	Up to 55 kW (75 hp) / 375 Nm with high-torque approach: low-end torque 23% higher than market average. Specific high-performance version designed for 75 kW (100 hp) / 415 Nm.	Prompt engine response & high productivity.
Compactness	3.4 L performance in a 2 L package. Compact after-treatment system (ATS) with simple installation and layout.	Matches both space and performance driven applications.
Ease of use and low cost of ownership	Single side serviceability and up to 600-hour service interval.	Low running costs and easier maintenance.
Multipower & Modularity	Ready for Natural Gas & Hybrid, with a modular design sharing common base components with Diesel.	Same installation interfaces and interoperability within engines.

THE F5 SERIES

From 43 to 105kW

Architecture
4 CYL, 3,4 - 3,6 L
displacements.

Torque
Up to 600 Nm.

**After Treatment
System**
HI-eSCR2
(above 55kW).

Service
600 hours service
intervals.



In agricultural machines, constant innovation is key. Even as size requirements for compact equipment grow more demanding, ever-higher productivity is needed on the fields. New technology boosts performance within existing layout constraints.

FPT Industrial's solutions increase engine displacement with no change in external dimensions. Better turbocharger and piston designs bring more power and outstanding torque density for the F5 series.

Our innovative products liberate resources by reducing costs for farmers and providing simpler maintenance over the lifecycle.

F34



F36



Engine Specifications

Model	Cyl Arrangement Air Handling	Turbocharging	Injection System	Displacement (Liters)
F34	4L/TCA	WG	Common Rail	3,4
F34	4L/TCA	WG	Common Rail	3,4
F34	4L/TC	WG	Common Rail	3,4
F36	4L/TCA	WG	Common Rail	3,6
F36	4L/TCA	WG	Common Rail	3,6
F36	4L/TCA	WG	Common Rail	3,6
F36	4L/TCA	WG	Common Rail	3,6

Power			Torque		Emission Standard	Exhaust System
(kW)	(hp)	(RPM)	(Nm)	(RPM)		
43	58	2500	250	1400	Stage V	DOC+DPF
55	75	2500	424	1200	Stage V	DOC+DPF
55	75	2500	314	1400	Stage V	DOC+DPF
63	86	2300	354	1400	Stage V	HI-eSCR2
75	102	2200	430	1400	Stage V	HI-eSCR2
90	122	2300	490	1400	Stage V	HI-eSCR2
105	143	2300	600	1500	Stage V	HI-eSCR2

Legend

Preliminary engine data for F36 above 56kW.
Max engine capability indicated for F34
below 56kW.

Air Intake
TCA Turbocharged After Cooled

Turbocharging
WG Fixed geometry turbocharger
with WasteGate valve

The Power of Density

Agricultural machines are constantly looking for improved performance, to grant higher productivity to end users yet complying with stringent dimension requirements on compact equipment. Diesel engines are therefore challenged to deliver growing performance within existing layout constraints, improving power and torque density through new technologies.

The FPT solution for light and midrange applications above 56kW (75hp) is the new F36 Stage V, increasing engine displacement from 3,4 to 3,6 L with no changes in external dimensions, thus ensuring unchanged compactness. Improved engine hardware includes new turbocharger and optimized piston design to cope with higher performance, increasing power output by 14% (up to 105kW / 143hp) and torque by 20% (up to 600 Nm), setting best in class torque density in its class.

The lowest EGR rate in the market (<10%) enables to reduce after-treatment dimension by up to 20%; overall after-treatment packaging is unchanged between Stage IV and Stage V, avoiding machine redesign across emission stages.

Sharing the same robust design approach, F34 with 3,4 L displacement covers application below 56kW (75hp) with prompt engine response and high torque output to ensure quick engine reaction to variable loads in compact machineries. Up to 600 hours oil change interval and one-side service ability reduce operating costs and simplify maintenance operations over lifecycle.

Key Advantages

	Features	Benefits
Performance	New 3,6 L displacement with 14% higher power and 20% more torque vs. Stage IV. Torque density leadership (+15% than competitors' avg.). 424 Nm output for F34.	Higher output within same engine dimensions. Prompt engine response for all applications, also below 56kW.
Compactness	The lowest EGR rate in the market (<10%). No changes in engine and ATS dimensions nor in cooling package.	20% reduction in ATS and urea tank dimensions for F36 above 56kW. Same installation for Stage IV and Stage V footprint.
Ease of use and low cost of ownership	Best in class 600h service intervals with one-side filters access. Maintenance-free HI-eSCR2 system.	Safe, easy and fast maintenance operations. Reduced operating costs & maximized vehicle uptime.

THE NEF SERIES

From 66 to 250kW

Architecture

4 CYL, 4,5 L displacement / 6 CYL, 6,7 L displacement.

Torque


Up to 1400 Nm.

After Treatment System

HI-eSCR2

Service

1200 hours service intervals.



Our NEF series boosts productivity in agriculture. More than 2 million engines sold attest to FPT Industrial's leadership since 2001.

NEF boasts best-in-class power and torque performance, fuel efficiency and reliability. It is highly flexible, with 4 and 6 cylinder configurations, featuring non-structural design.

The new Stage V NEF series marks an additional leap in efficiency. With no change in engine size and layout, innovative designs in cylinder head, pistons and turbochargers raise the performance further, leaving the competition behind.

N45



N67



Engine Specifications

Model	Cyl Arrangement Air Handling	Turbocharging	Injection System	Displacement (Liters)
N45	4L/TCA	WG	Common Rail	4,5
N45	4L/TCA	WG	Common Rail	4,5
N45	4L/TCA	WG	Common Rail	4,5
N67	6L/TCA	WG	Common Rail	6,7
N67	6L/TCA	WG	Common Rail	6,7
N67	6L/TCA	WG	Common Rail	6,7
N67	6L/TCA	WG	Common Rail	6,7
N67	6L/TCA	eVGT	Common Rail	6,7

Power			Torque		Emission Standard	Exhaust System
(kW)	(hp)	(RPM)	(Nm)	(RPM)		
89	121	2200	549	1500	Stage V	HI-eSCR2
103	140	2200	640	1500	Stage V	HI-eSCR2
125	170	2200	710	1500	Stage V	HI-eSCR2
147	200	2100	744	1400	Stage V	HI-eSCR2
129	175	2200	802	1500	Stage V	HI-eSCR2
151	205	2200	940	1500	Stage V	HI-eSCR2
191	260	2200	1159	1500	Stage V	HI-eSCR2
212	288	2200	1160	1500	Stage V	HI-eSCR2
250	340	2100	1400	1400	Stage V	HI-eSCR2

Legend

Power refers to engine rated speed, except for max engine capability (260kW peak)

Air Intake
TCA Turbocharged After Cooled

Turbocharging
WG Fixed geometry turbocharger with WasteGate valve
eVGT Electronic Variable Geometry Turbocharger

Productivity Leader

Developed to satisfy the most demanding productivity requirements of agricultural missions, the NEF Series marks FPT Industrial technological excellence since 2001, strong of more than 2 million engines produced. Featuring best-in-class power and torque performance, fuel efficiency and reliability, the NEF Series stands out for its flexibility, available in 4 (N45) and 6 (N67) cylinders configurations, with non-structural and structural design.

In its continuous commitment to provide leading products and improved solutions, FPT Industrial introduces the new Stage V NEF Series setting a further step towards higher productivity. Maintaining the same engine dimensions and layout of previous versions, cylinder head, pistons and turbochargers have been redesigned for performance increase: up to 147 kW on N45 (+14%) 250 kW to deliver best in class power and torque density (up to +14% Vs. competitors average).

New filters with increased capacity and clogging sensor are capable of up to 1200 hours service interval, the longest in the market and twice the previous interval. This new feature comes along with the innovative HI-eSCR2 after-treatment system, which comply with Stage V regulations with a maintenance-free, contributing to low operating costs.

Proven and further enhanced EGR free combustion guarantees the fuel efficiency of NEF Series, together with additional improvements in fluid consumption, leveraging on reduced frictions for leading efficiency compared to competitors using EGR and DPF.

Lean design with no EGR and single stage turbocharging, available both as fixed or variable geometry, is a made-to-last solution ensuring maximum reliability. Thanks to the dimension-neutral approach granted by HI-eSCR2, Stage V solution features unchanged packaging and same cooling requirement compared to Stage IV.

Key Advantages

	Features	Benefits
Performance	Best in class power and torque density : up to +14% vs. competitors average in 6-liters engine range.	Performance increase with same engine displacement and no layout changes. Maximized power, torque and transient response
Low TCO	New high capacity filters with clogging sensor. Maintenance-free ATS. New piston rings design & advanced machining process	Best in class service interval up to 1200 hours. Low running costs over lifecycle. Reduced oil consumption.
Reliability	Lean design with no EGR and single stage turbocharging solution.	Proven system reliability. Robustness and durability.
Flexibility	No changes in cooling package required.	Unique solution across emission stages (Stage IIIA to StageV).



Our range of safe, reliable solutions for all agricultural applications improves efficiency and productivity.

THE CURSOR SERIES

From 210 to 570kW

Architecture

6 CYL , 8,7 - 12,9 -
15,9 L displacements.

Torque

Up to 3320 Nm.

**After Treatment
System**

HI-eSCR2

Service

600 hours service
intervals.



The CURSOR family responds to the most demanding heavy-duty needs in a wide range of agriculture applications from 210 to 570 kW.

Through ongoing innovation, these engines have constantly kept up with a growing demand for performance and with stricter emission regulations.

Research-driven advances have led to innovative technical contents, including variable-geometry turbochargers, high-pressure common rail injection, new materials and breakthrough after-treatment technologies.

CURSOR 9



CURSOR 13



CURSOR 16



Engine Specifications

Model	Cyl Arrangement Air Handling	Turbocharging	Injection System	Displacement (Liters)
Cursor 9	6L/TCA	WG	Common Rail	8,7
Cursor 9	6L/TCA	WG	Common Rail	8,7
Cursor 13	6L/TCA	WG	Common Rail	12,9
Cursor 13	6L/TCA	WG	Common Rail	12,9
Cursor 13	6L/TCA	WG	Common Rail	12,9
Cursor 16	6L/TCA	WG	Common Rail	15,9
Cursor 16*	6L/TCA	WG	Common Rail	15,9

Power			Torque		Emission Standard	Exhaust System
(kW)	(hp)	(RPM)	(Nm)	(RPM)		
245	333	2100	1510	1500	Stage V	HI-eSCR2
275	374	2100	1675	1500	Stage V	HI-eSCR2
308	419	2100	1800	1500	Stage V	HI-eSCR2
346	471	2100	2012	1400	Stage V	HI-eSCR2
384	522	2100	2300	1400	Stage V	HI-eSCR2
407	554	2100	2400	1400	Stage V	HI-eSCR2
480	653	2100	2751	1500	Stage V	HI-eSCR2
515	700	2100	2988	1500	Stage V	HI-eSCR2

Legend

* Max performance on Cursor16: 570kW @ 2100 rpm/ 3.320Nm @ 1500 rpm
Power refers to engine rated speed

Air Intake
TCA Turbocharged After Cooled

Turbocharging
WG Fixed geometry turbocharger with WasteGate valve

Designed to Go Beyond

Developed for the most demanding heavy duty needs, the Cursor series provides robust design for highly intensive missions in a wide range of construction applications from 210 to 570 kW. First launched in 1998, the Cursor range has gone through continuous improvements to keep pace with growing market requirements in performance and efficiency, while complying with stricter emission regulations and always offering innovative technical contents, such as variable-geometry turbochargers, high-pressure common rail injection, new materials and breakthrough after-treatment technologies.

All Cursor engines share 6 cylinder architecture and EGR-free technology, ensuring optimal engine output with highly efficient combustion, resulting in effective performance and low cooling requirements, unchanged from Stage IIIA to Stage V for smart synergies across machine layouts. Moreover, all engines meet Stage V regulation with maintenance-free HI-eSCR2 system, the latest generation of FPT's longstanding experience in after-treatment technology, proven by more than 1 million systems sold to date. With no need to replace the filter over the lifecycle, and with oil change intervals of up to 600 hours, running costs are minimized.

The Cursor 9, with an 8.7-litre displacement, is a compact and yet powerful solution in the 210 to 338 kW range, equipped with a 1800-bar common rail system, and a fixed or variable geometry turbocharger, guaranteeing a prompt engine response and excellent power density (up to 7% better than the market average).

With 12,9 lt, Cursor 13 features heavy-duty 2200bar common rail system and newly designed engine hardware for maximized robustness and durability. With single and high-performance two stage-turbo on Cursor13, this engine cover range from 300 to 515kW peak.

Awarded as Diesel of the Year in 2014, Cursor 16 is the latest addition to the Cursor range, with 15,9 liters displacement and up to 570kW delivering 18 liters-like performance in a 13 liters package, with leading power-to-weight ratio (0,5 hp/kg). 2200 bar common rail system, innovative ball-bearing turbocharger, high-resistance cylinder head in compacted graphite iron (CGI) and more than 20.000 hours of bench-test specifically dedicated to off-road missions, make the Cursor16 a strong, reliable yet compact solution.

Key Advantages

	Features	Benefits
Performance	Portfolio for any mission. Leading power density with up to +7% Vs. market average in 9 L range. No EGR architecture.	Wide engine range covering up to 570kW. Effective performance. Maximized power, torque and transient response.
Low Operating Costs	EGR-free combustion. Maintenance-free ATS. Extended oil service intervals.	Optimized fluid efficiency. Low running costs over lifecycle. Maximum uptime: 600 hours service intervals.
Reliability	Heavy-duty design with high pressure common rail injection. Lean design with no EGR and single stage turbocharging solution.	Proven system reliability.
Flexibility	No changes in cooling package required.	(StageIIIA to StageV). Unique solution across emission stages.

THE V SERIES

Up to 670kW

Architecture
8 CYL V, 20 L
displacement.

Torque
Up to 4095 Nm.

**After Treatment
System**
HI-eSCR

Service
600 hours service
intervals.



The V20 engine is a testimony to FPT Industrial's excellence in hi-tech, reliable products that create value for users in the field. The new flagship 20-litre engine has a lean V8 architecture, with a highly compact layout and low engine weight. Superior efficiency is combined with reduced engine friction. An innovative Stage V after-treatment solution curbs operating costs and downtime.

Robust engine design is coupled with new cast-iron components and advanced materials. Solidity goes hand in hand with unflinching performance, in all conditions.

V20



Engine Specifications

Model	Cylinder Arrangement Air Handling	Turbocharging	Injection System	Displacement (Liters)
V20	8V/TCA	WG (1 x bank)	Common Rail	20.1

Power			Torque		Emission Standard	Exhaust System
(kW)	(hp)	(RPM)	(Nm)	(RPM)		
670	910	1800	4095	1500	Stage V	SCR

Legend

Arrangement
V V-configuration (90°)

Turbocharging
WG Fixed geometry turbocharger with WasteGate valve

Exhaust System
SCR Selective Catalytic Reduction

Air Intake
TCA Turbocharged After Cooled

Power without Compromise

In order to provide hi-tech reliable products designed for the toughest missions, FPT further extends its offering with the new V20, a compact yet high-performing engine with up to 670kW power output.

The brand's new flagship 20-litre engine features an enhanced V8 architecture, with a 90° angle between cylinder banks, resulting in highly compact layout and low engine weight to ensure space-optimized installations while guaranteeing the right power is available in every condition, thanks to advanced engine hardware and two turbochargers optimized for any working point.

With its EGR-free, optimized combustion, the V20 boasts superior efficiency, together with V8 layout reducing engine friction compared to more

complex V12 architectures. Operating costs and uptime are ensured by the maintenance-free Tier 4 Final and Stage V-ready after-treatment solution, an SCR-only system based on longstanding FPT experience in SCR technology, requiring no need for maintenance over lifecycle.

To grant the highest robustness, engine design shares 2200-bar common rail system and key components with reliability-proven Cursor engine series; furthermore, the newly designed 220 bar in-cylinder pressure-capable engine structure adopts new cast-iron components and advanced materials on valves, crankshaft and compressor wheel.

The new V20 comes with a 670 kW power and a max torque of 4095 Nm, ensuring unfailing performance output in all conditions.

Key Advantages

	Features	Benefits
Performance	0,6 hp/kg power-to-weight ratio (+13% & Compactness Vs. avg. V12 competitors). No EGR & 220 bar of in-cylinder pressure. High To resistant turbochargers.	The most compact high-performance engine optimized combustion. Uncompromised performance output in all conditions.
Efficiency & Total Cost of Ownership	EGR-free architecture & 2200 bar-capable Common Rail system. Cross-bank turbocharger configuration.	Maximum engine efficiency.
	DPF-free after-treatment system. Optimized fluid dynamics.	No need for maintenance - maximum uptime.
Robustness & Reliability	Steel pistons and high-pressure injection system from Cursor series. New advanced materials on valves, crank shaft, turbochargers, head.	Proven reliability. Optimized engine structure.
	SCR-only and DPF-free after-treatment solution.	Effective emission-compliance.



**We increase the benefits
for end users and the
environment while creating
value for businesses.**

THE POWER PACK

ATS Smart Installation Package

The Power Pack is our new, smart installation solution. All key after-treatment components fit into one compact, pre-assembled set, mounted on the engine. A wide set of options can be easily custom applied to fit a wide range of applications.

This is an ideal response to the lower emission limits entailed by Stage V legislation. Compliance and machine upgrade become easier, for variety industrial applications.

THE POWER PACK

F28



F36



N67



C9



Emissions Compliance Made Easy

Stage V legislation will bring a further reduction on emission limits and extend regulation also to stationary applications and power ranges currently at Stage IIIA, thus requiring a wide range of applications to upgrade to this next emission step.

FPT introduces a new, smart installation solution, enclosing all key after-treatment components into a single package: DOC, HI-eSCR2, AdBlue injection system and all required sensors, together with manifolds, are included in a compact and pre-assembled pack avoiding the need of a dedicated exhaust system design. The pre-packed solution, moreover, offers FPT's pre-validated design in terms of fluid-dynamics, manifold layout and sensors position in order to make final validation process lean and easier.

All electrical signals and connection are managed by a single cable for fast, reliable, and quick connection to engine and machine electronic management system.

All productivity benefits of FPT Industrial technology, in terms of performance and efficiency, together with the innovative HI-eSCR2 system ensuring Stage V compliance with a maintenance-free solution, comes in a simple and flexible package.

Key Advantages

	Features	Benefits
Robustness	Fully pre-packed solution.	No specific exhaust system design.
Installability	Engine mounted solution; from 12 after treatment components to 1 package/all signals into a single cable.	Quick installation solution.
Flexibility	Robust pre-validated package. Lean application sign-off.	Smart installation package. Easy emission upgrade.



All the pictures, drawings illustrations and descriptions contained in this brochure are based on product information available to FPT Industrial at the time of printing (30/09/2022). Some of the engine line-ups may refer to a specific market configuration which may not be present or offered for sale available in all other markets. The colors featured in this brochure may differ from the originals. FPT Industrial reserves the right to introduce any modifications, at any time and without any prior advance notice, to design, material, components equipment and/or technical specifications.

FPT Industrial S.p.A.

Via Puglia 15, 10156
Torino, Italy

fptindustrial.com

[marketing@
fptindustrial.com](mailto:marketing@fptindustrial.com)

All the pictures, drawings illustrations and descriptions contained in this brochure are based on product information available to FPT Industrial at the time of printing (30/07/2022). Some of the engine line-ups may refer to a specific market configuration which may not be present or offered for sale available in all other markets. The colors featured in this brochure may differ from the originals. FPT Industrial reserves the right to introduce any modifications, at any time and without any prior advance notice, to design, material, components equipment and/or technical specifications.