

**FPT ePowertrain solutions**

Innovation and sustainability have always been fundamental characteristics of FPT Industrial. In order to remain at the forefront of technological advancements and effectively respond to market needs, the Brand created ePowertrain department in 2018. With main hubs based in the R&D centers in Arbon, Switzerland, Coventry, UK and Turin, Italy, the ePowertrain department is focused on developing the powertrains of tomorrow, today. Being a global leader means setting new targets that grow more challenging every day. To reach them, we have drawn on our expertise along with the best innovative start-ups worldwide, through partnerships, acquisitions and joint ventures. Now, we can proudly display the results, showcasing our full range of eDriveline and Battery Storage and Management solutions.



**Electric Driveline**

FPT Industrial is responding to the crucial challenges of transport sustainability, energy transition and CO<sub>2</sub> emission reduction with a complete range of innovative products. Designed to fully integrate all ePowertrain elements into a compact solution, capable of accommodating both the commercial load and the battery packs, the new eAxles and Central Drive offer outstanding performance and reliability, according to the mission application.

**Specifications**

<b>Model:</b>	eCD 140
<b>Application:</b>	LCV - Minibus
<b>Type:</b>	Central Drive
<b>n. eMotors:</b>	1
<b>Peak Power (kW):</b>	140
<b>Peak Torque (Nm):</b>	450
<b>Peak Axle Torque (Nm):</b>	1.600
<b>DC Voltage (V):</b>	340 - 450
<b>GAW (ton):</b>	-
<b>GVW (ton):</b>	8
<b>System efficiency:</b>	>93%
<b>Weight (kg):</b>	117
<b>Dimensions (mm):</b>	536 x 382 x 355
<b>Power Density (kW/kg):</b>	1,20
<b>Gear - n. speed:</b>	1
<b>Gear ratio:</b>	4
<b>Parking lock system:</b>	Yes - 30% max slope
<b>Durability Be10 (km):</b>	up to 350.000

**eDRIVELINE - CENTRAL DRIVE**



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

**FPT ePowertrain solutions**

Innovation and sustainability have always been fundamental characteristics of FPT Industrial. In order to remain at the forefront of technological advancements and effectively respond to market needs, the Brand created ePowertrain department in 2018. With main hubs based in the R&D centers in Arbon, Switzerland, Coventry, UK and Turin, Italy, the ePowertrain department is focused on developing the powertrains of tomorrow, today. Being a global leader means setting new targets that grow more challenging every day. To reach them, we have drawn on our expertise along with the best innovative start-ups worldwide, through partnerships, acquisitions and joint ventures. Now, we can proudly display the results, showcasing our full range of eDriveline and Battery Storage and Management solutions.



**Electric Driveline**

FPT Industrial is responding to the crucial challenges of transport sustainability, energy transition and CO<sub>2</sub> emission reduction with a complete range of innovative products. Designed to fully integrate all ePowertrain elements into a compact solution, capable of accommodating both the commercial load and the battery packs, the new eAxles and Central Drive offer outstanding performance and reliability, according to the mission application.

**Specifications**

<b>Model:</b>	eCD 140
<b>Application:</b>	LCV - Minibus
<b>Type:</b>	Central Drive
<b>n. eMotors:</b>	1
<b>Peak Power (kW):</b>	140
<b>Peak Torque (lb-ft):</b>	332
<b>Peak Axle Torque (lb-ft):</b>	1,180
<b>DC Voltage (V):</b>	340 - 450
<b>GAW (lb):</b>	-
<b>GVW (lb):</b>	17,600
<b>System efficiency:</b>	>93%
<b>Weight (lb):</b>	258
<b>Dimensions (inch):</b>	21.1 x 15.03 x 13.97
<b>Power Density (kW/lb):</b>	0.54
<b>Gear - n. speed:</b>	1
<b>Gear ratio:</b>	4
<b>Parking lock system:</b>	Yes - 30% max slope
<b>Durability Be10 (mi):</b>	up to 217,500

**eDRIVELINE - CENTRAL DRIVE**



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE