

SPECIFICATIONS


No. of cylinders / valves	6L / 4		
Injection System	COMMON RAIL		
Turbocharger	VGT		
Displacement	liters	6.7	
Bore x Stroke	millimeters	104 x 132	
Max power	kW (HP) @ rpm	250 (340) @ 1800	
Max Torque	Nm @ rpm	1398 @ 1400	
ATS	HI-eSCR2		
Certification	Stage V - Tier 4 Final		

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1060 x 669 x 927	
Dry Weight	Kg	530	

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS

POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

AGRICULTURE

Do you want to know more?



LEGEND

Air Handling

- NA (Naturally Aspirated)
- TC (Turbocharged)
- TCA (Turbocharged with aftercooler)

Turbocharger

- WG (Wastegate)
- VGT (Variable Geometry Turbocharger)
- TST (Twin-Stage Turbocharger)

Exhaust System

- EGR (Exhaust Gas Recirculation)
- SCR (Selective Catalytic Reduction)
- DPF (Diesel Particulate Filter)
- DOC (Diesel Oxidation Catalyst)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

