Stage V - Tier 4 Final

POWER GENERATION G-Drive F34

SPECIFICATIONS

| Certification | | | Stage V - Tier 4 Final |
|---------------------------|--------|-----|------------------------|
| No. of cylinders | | | 4L |
| Injection System | | | ECR |
| Air Intake | | | TC |
| Displacement | liters | | 3.4 |
| Exhaust System | | | DOC - DPF |
| Stand-by Power @ 1500 rpm | | kWm | 37 |
| Prime Power @ 1500 rpm | | kWm | 33 |
| Stand-by Power @ 1800 rpm | | kWm | 39 |
| Prime Power @ 1800 rpm | | kWm | 35 |
| Code | | | - |

WEIGHT AND DIMENSIONS

| Dimensions (L x W x H) | mm | 1217 x 741 x 963 |
|------------------------|----|------------------|
| Dry Weight | Kg | - |

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Arrangement L (in line)

V (90° "V" configuration)

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Injection System

M (Mechanical)

ECR (Electronic Common Rail)

EUI (Electronic Unit Injector)

MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



