OFF ROAD Agriculture F34

55 kW (75 HP) @ 2500 rpm Stage V - Tier 4 Final


SPECIFICATIONS

No. of cylinders / valves		4L / 2
Injection System		COMMON RAIL
Turbocharger		WG (TC)
Displacement	liters	3.4
Bore x Stroke	millimeters	99 x 110
Max power	kW (HP) @ rpm	55 (75) @ 2500
Max Torque	Nm @ rpm	314 @ 1400
ATS		DOC+DPF
Certification		Stage V - Tier 4 Final

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	690 x 603 x 902
Dry Weight	Kg	315

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharger)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DOC (Diesel Oxidation Catalyst)

DPF (Diesel Particulate Filter)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE



