

SPECIFICATIONS


No. of cylinders / valves	6L / 4	
Injection System	ECR	
Turbocharger	WG	
Displacement	liters	12.9
Bore x Stroke	millimeters	135 x 150
Max power	kW (HP) @ rpm	302 (411) @ 1900
Max torque	Nm @ rpm	2120 @ 1200
ATS	DOC + DPF + SCR + CUC	
Certification	Euro VI E	

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1360 x 1008 x 1171
Dry Weight	Kg	1132

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS

POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

TRUCKS

Do you want to know more?



LEGEND

Turbocharger

e-VGT (Electronic Variable Geometry Turbo)

2stT (Twin-Stage Turbo)

WG (Fixed Geometry Turbocharger with Waste Gate valve)

Injection System

EUI (Electronically Controlled Unit Injector)

MPI (Multi-Points Injection)

ECR (Electronic Common Rail)

Exhaust System

ATS (Aftertreatment System)

CCDPF (Cross Coupled Diesel Particulate Filter)

CUC (Clean Up Catalyst)

DOC (Diesel Oxidation Catalyst)

SCR (Selective Catalytic Reduction)

DPF (Diesel Particulate Filter w/ passive regeneration)

EGR (External Exhaust Gas Recirculation)

HPEGR (High Pressure Cooled External EGR)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

