OFF ROAD Agriculture F36

90 kW (122 HP) @ 2300 rpm Stage V - Tier 4 Final

SPECIFICATIONS

No. of cylinders / valves		4L / 4
Injection System		COMMON RAIL
Turbocharger		WG (TCA)
Displacement	liters	3.6
Bore x Stroke	millimeters	102 x 110
Max power	kW (HP) @ rpm	90 (122) @ 2300
Max Torque	Nm @ rpm	490 @ 1400
ATS		Compact HI-eSCR2
Certification		Stage V - Tier 4 Final

WEIGHT AND DIMENSIONS


Dimensions (L x W x H)	mm	702 x 614 x 898
Dry Weight	Kg	320

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

POWER & TORQUE



Do you want to know more?

LEGEND

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharger)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DOC (Diesel Oxidation Catalyst)

DPF (Diesel Particulate Filter)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE



