

SPECIFICATIONS

No. of cylinders / valves	4L/2
Injection System	MECHANICAL
Turbocharger	WG (TC)
Displacement	liters 4.5
Bore x Stroke	millimeters 104 x 132
Max power	kW (HP) @ rpm 66 (90) @ 2200
Max Torque	Nm @ rpm 400 @ 1250
ATS	i-EGR
Certification	Stage III A - Tier 3

WEIGHT AND DIMENSIONS


Dimensions (L x W x H)	mm	810 x 676 x 901
Dry Weight	Kg	410

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

POWER & TORQUE



AGRICULTURE

Do you want to know more?



LEGEND

Air Handling

- NA (Naturally Aspirated)
- TC (Turbocharged)
- TCA (Turbocharged with aftercooler)

Turbocharger

- WG (Wastegate)
- VGT (Variable Geometry Turbocharger)
- TST (Twin-Stage Turbocharger)

Exhaust System

- EGR (Exhaust Gas Recirculation)
- SCR (Selective Catalytic Reduction)
- DPF (Diesel Particulate Filter)
- DOC (Diesel Oxidation Catalyst)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

