397 kW (540 HP) @ 1900 rpm

CURSOR 13

OFF ROAD Agriculture CURSOR 13

SPECIFICATIONS

No. of cylinders / valves		6L / 4
Injection System		COMMON RAIL
Turbocharger		WG (TCA)
Displacement	liters	12.9
Bore x Stroke	millimeters	135 x 150
Max power	kW (HP) @ rpm	397 (540) @ 1900
Max Torque	Nm @ rpm	2300 @ 1400
ATS		HI-eSCR2
Certification		Stage V - Tier 4 Final

WEIGHT AND DIMENSIONS


Dimensions (L x W x H)	mm	1355 x 953 x 1213
Dry Weight	Kg	1320

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

POWER & TORQUE



Do you want to know more?

LEGEND

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharger)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DOC (Diesel Oxidation Catalyst)

DPF (Diesel Particulate Filter)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE



