

SPECIFICATIONS


No. of cylinders / valves	6L / 4	
Injection System	COMMON RAIL	
Turbocharger	WG (TCA)	
Displacement	liters	6.7
Bore x Stroke	millimeters	104 x 132
Max power	kW (HP) @ rpm	201 (273) @ 2000
Max Torque	Nm @ rpm	1160 @ 1500
ATS	HI-eSCR	
Certification	Stage IV - Tier 4 Final	

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1065 x 687 x 1071
Dry Weight	Kg	527

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS

POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

AGRICULTURE

Do you want to know more?



LEGEND

Air Handling
NA (Naturally Aspirated)
TC (Turbocharged)
TCA (Turbocharged with aftercooler)

Turbocharger
WG (Wastegate)
VGT (Variable Geometry Turbocharger)
TST (Twin-Stage Turbocharger)

Exhaust System
EGR (Exhaust Gas Recirculation)
SCR (Selective Catalytic Reduction)
DPF (Diesel Particulate Filter)
DOC (Diesel Oxidation Catalyst)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

